airmet F: 1 F: 1 F: 1

 Distributed by: Air-Met Scientific Pty Ltd

 Air-Met Sales/Service
 Air-Met Sales/Service

 P: 1800 000 744
 P: 13

 F: 1800 000 774
 E: hir

 E: sales@airmet.com.au
 W: w

Air-Met Rental P: 1300 137 067 E: hire@airmet.com.au W: www.airmet.com.au

NOISE INDICATOR NI-100

The Noise Indicator NI-100 alerts users to potentially dangerous noise levels, helping identify areas where further noise assessment or hearing protection may be needed. Users clip the device to a shirt or jacket and its LED light delivers a clear indicator when noise levels exceed a potentially hazardous threshold. Its small size and lightweight design make it ideal for workers in a variety of industries.

Features and Benefits

- + Provides visual "Go/No Go" indication of noise levels below or above 85 dBA
- + Flashing green indicates noise level is below 85 dBA and flashing red indicates noise level is above 85 dBA and hearing protection may be needed
- + Simple one-button operation with a rechargeable battery
- + Small and lightweight
- + Clips to lapel or shirt pocket
- + Provides an affordable training tool for helping workers know when hearing protection may be required
- + Increase awareness of hearing conservation guidelines
- + Can be used as a mapping tool to qualify future noise studies





SPECIFICATIONS

NOISE INDICATOR NI-100

Size

Weight Temperature Operating/Storage Humidity Range Accuracy Alert Level Battery **Battery Life**

Charging

Auto-Power Off

2" (L) x 1.4" (W) x 0.5" (D) / 5.1 cm (L) x 3.6 cm (W) x 1.3 cm (D) 0.6 oz (17 g)

-14 to 122°F / -10 to 50°C 0 to 95%; non-condensing ЗdВ Flashes red when >85 dBA Flashes green when <85 dBA Li-Poly (flat cell)* with approximately 200 hours of operating before recharging Approximately two years of charging cycles A mini-USB cable (sold separately) plugs into bottom port of device The device will power off after approximately 10 hours

*Not certified intrinsically safe

Specifications are subject to change without notice.

Quest is a trademark, and TSI and the TSI logo are registered trademarks of TSI Incorporated.



One-button operation

- + Simply clip to lapel and power-on
- + Easy for workers to use and understand

Small Size

+ Compact, lightweight design for increased hearing protection compliance

Visual "Go/No Go"

- + Green LED ("Go") flashes when noise level is below 85 dBA
- + Red LED ("No Go") flashes when noise level exceeds 85 dBA
- + Easy-to-understand visual indication when hearing protection may/may not be needed

Rechargeable battery

- + Provides up to 200 hours of use between charges
- + 10-hour auto-power off helps prolong battery life for extra cost savings



TSI Incorporated - Visit our website www.tsi.com for more information.

Tel: +1 800 874 2811 USA UK Tel: +44 149 4 459200 Tel: +33141192199 France Germany Tel: +49 241 523030

India China

Tel: +91 80 67877200 Tel: +86 10 8219 7688 Singapore Tel: +65 6595 6388



Distributed by: Air-Met Scientific Pty Ltd Air-Met Sales/Service P: 1800 000 744 F: 1800 000 774 E: sales@airmet.com.au

Air-Met Rental P: 1300 137 067 E: hire@airmet.com.au W: www.airmet.com.au