

# SM70

## Fixed Monitor

With an integrated LCD display, audible alarm, relay outputs, and a choice of sensor ranges in both ozone and VOC gases – the SM70 offers unbeatable value for industrial and indoor gas monitoring.

Benefitting from the accuracy of Aeroqual's proprietary GSS sensors, our customers use the SM70 in many indoor and industrial applications including: leak detection, health and safety monitoring, and process control.

### Features

- Large format digital display
- Replaceable GSS sensors
- External control outputs
- High and low alarms
- Power adaptor/charger included



### Specifications

|                             |   |
|-----------------------------|---|
| Sensor type                 | Analytic GSS Technology®<br>Gas Sensitive Semiconductor   |
| Sensor specifications       | Available with ozone or VOC sensors in various ranges. Please refer to sensor specification table at <a href="http://www.aeroqual.com">www.aeroqual.com</a> . |
| Sampling method             | Active sampling   |
| Operational mode            | Continuous Control or Alarm   |
| Operating temperature       | 0°C to 40°C   |
| Operating relative humidity | 10% to 90% non-condensing   |
| Warm up time                | 10 minutes  |
| Display                     | 3.5 digit LCD   |
| Relay set point             | User configurable   |
| Digital output              | RS232 and RS485   |
| Analog output               | 0 - 5 VDC (8 bit)   |
| Relay output                | 24 V; 5A (max.)   |
| Buzzer alarm (optional)     | Internal piezo 85 db @ 30 cm  |
| Power supply                | 12 VDC; 800 mA; Plug-in AC power adaptor supplied   |
| Enclosure rating            | IP20 & NEMA 1 equivalent  |
| Enclosure dimensions        | 130 W x 94 H x 57 D (mm); 5 1/8 W x 3 3/4 H x 2 1/4 D (in)  |
| Enclosure casing            | Flame resistant thermoplastic PS  |
| Enclosure mounting          | Screw fix   |
| Weight                      | < 270 g; 9.5 oz (excludes AC power adaptor)   |
| Approvals                   | Part 15 of FCC Rules, EN 61000-6-3: 200, EN 61000-6-1: 2001   |