



VENTIS SLIDE-ON PUMP

SPECIFICATIONS*

INSTRUMENT WARRANTY

Two-year warranty, excluding consumables (i.e. – filters)

CASE MATERIAL

Polycarbonate with protective rubber overmold

SAMPLE DRAW CAPABILITY

Up to 15.2 m (50 ft)

DIMENSIONS

143 x 81 x 68 mm (5.6 x 3.2 x 2.7 in) Lithium-ion battery version 143 x 81 x 85 mm (5.6 x 3.2 x 3.3 in) Extended range lithium-ion battery version 143 x 81 x 73 mm (5.6 x 3.2 x 2.9 in) Alkaline battery version

WEIGHT

270 g (9.5 oz) Lithium-ion battery version 316 g (11.2 oz) Extended range lithium-ion battery version 284 g (10.0 oz) Alkaline battery version

OPERATING TEMPERATURE RANGE

-20 °C to 50 °C (-4 °F to 122 °F)

OPERATING HUMIDITY RANGE

15%-95% non-condensing (continuous)

POWER SOURCE/RUN TIME

Rechargeable lithium-ion battery pack, 18 hours @ 20 °C Rechargeable extended range lithium-ion battery pack, 36 hours @ 20 °C Replaceable AAA alkaline battery pack, 10 hours @ 20 °C

PUMP FAULT ALARMS

Ultra-bright LEDs Loud audible alarm (90 dB at 30 cm)

IP RATING

Third-party certified IP67

CERTIFICAT	IIUN2
UL:	Class I, Division 1, Groups A B C D, T4;
	Class I, Zone O, AEx ia IIC T4 Ga;
	Class II, Group F G (Carbonaceous and Grain Dust)
CSA:	Class I, Division 1, Group A B C D, T4
	Ex ia IIC T4
ATEX:	Ex ia I Ma and Ex ia IIC T4 Ga;
	Equipment Group and Category: I M1 and II 1G
IECEx:	Ex ia IIC T4 Ga
INMETRO:	Ex ia IIC T4 Ga; IP66; IP67
GOST-EAC:	0 Ex ia IIC X T4
	PO Ex ia I X
China Ex:	Ex ia IIC T4 Ga

*All specifications are based on a typical instrument and typical performance of the instrument, and are subject to variability.





Distributed by: Air-Met Scientific Pty Ltd Air-Met Sales/Service P: 1800 000 744 F: 1800 000 774 E: sales@airmet.com.au

Air-Met Rental P: 1300 137 067 E: hire@airmet.com.au W: www.airmet.com.au

The Ventis[™] Slide-on Pump is ideally suited for operators who wear their gas monitors for personal protection but occasionally require a pump for confined space entries. Available in black or safety orange and powered by its own battery pack, the slide-on pump is compatible with the Ventis[™] MX4 and Ventis[™] Pro Series Multi-Gas Monitors.

- Convenient sampling Sample draw distance of up to 50 feet provides convenient sampling in a wide range of applications
- **Easy to attach** No tools are required to attach or remove the Ventis Slide-on Pump to or from the monitor
- Uses same battery packs and chargers as Ventis Monitor and pump each use the same battery packs, and can easily be exchanged between instruments
- Flexible battery options Three available battery options make this pump extremely flexible in the field



ACCESSORY ORDERING INFORMATION



VTSB-101 Lithium-ion Battery Kit



17151184-01 Extended Range Lithium-ion Battery Cover



17157329-0 Replacement Door



17151184-11

VTSB-111

Lithium-ion Battery Kit

17157329-1 Replacement Door

VENTIS SLIDE-ON PUMP – MODEL#VSP MATRIX

EXAMPLE : 18109162-1111 – Ventis Slide-on Pump, lithium-ion battery pack, safety orange, UL/CSA, EN-FR-ES-DE-CN	18109162-	1	1	1	1
DESCRIPTION	Base	Battery	Color	Approvals	Language
Ventis Slide-on Pump	18109162-				

Select options below in addition to base price

BATTERY

Lithium-ion battery pack 1					
Extended range lithium-ion battery pack		2			
Alkaline battery pack		3			
COLOR					
COLOR	I	I	I		
COLOR Black		 	0		

APPROVALS			
UL/CSA		1	I
ATEX/IECEx		2	
China EX		5	l
GOST-EAC		7	
INMETRO		9	

LANGUAGE

English, French, Spanish, German, Chinese		1
Italian, Polish, Czech, Portuguese, Russian		2



VTSB-201 Extended Range Lithium-ion Battery Kit



VTSB-211 Extended Range Lithium-ion Battery Kit

17154577-11

Alkaline Battery Kit, VSF



BATTERY

PART NUMBER	DESCRIPTION
VTSB-1XY	Lithium-ion battery kit
VTSB-2XY	Extended range lithium-ion battery kit
17148313-Y	Extended range lithium-ion battery pack
17151184-XY	Cover, extended range lithium-ion
17154577-XY	Alkaline battery kit, VSP

PUMP ACCESSORIES

17157329-X	Replacement door, Ventis Pro/Ventis MX4 compatible
18109207-10	Urethane sample tubing kit 3.048 m (10 ft)
17154853-5	Exhaust filter (5 pack)
17154581-5	Audible alarm filter (5 pack)

CHARGERS

18108191	Single-unit charger
18108209	Single-unit charger with datalink
18108650-A	6-unit charger
18108651	12 VDC Single-unit automotive charger with plug
18108652	12 VDC Single-unit truck-mount charger with plug
18108653	12 VDC Single-unit hard wired truck-mount charger

NOTE: Charger is not included with the Ventis Slide-on Pump

"X" denotes color where 0 = Black, 1 = Safety Orange

- "Y" denotes approvals where 1 = UL, CSA, ATEX, IECEx, INMETRO, and GOST-EAC; 3 = China EX
- "A" denotes power cord option 0 = US, 1 = UK, 2 = EU, 3 = AUS, 4 = ITA, 5 = DEN, 6 = SWZ

Rev 1 0317 | © 2017 Industrial Scientific Corporation



AMERICAS Phone: +1-412-788-4353 | Fax: +1-412-788-8353 1-800-DETECTS (338-3287) North America info@indsci.com

ASIA PACIFIC Phone: +65-6561-7377 Fax: +65-6561-7787 info@ap.indsci.com

EMEA

www.indsci.com

Phone:+33 (0)1 57 32 92 61 Fax: +33 (0)1 57 32 92 67 info@eu.indsci.com