

Patented* flow control system holds constant flow to ± 5% of set-point

- 1000 to 3000 ml/min flow range
- Low flows from 5 to 500 ml/min with low flow adapter kit

• Alkaline battery powered — no charging!

- Economical, disposable AA alkaline batteries
- Ready to go anytime!
- Ideal for abatement, indoor air sampling, and emergency response in non-hazardous locations

Minimum of 8 hours run time

• Up to 3000 ml/min and 10 inches water back pressure

Ordering Information

AirLite requires 1/4-inch ID tubing.

• Easy operation

- Turn it on, calibrate, and sample
- Easy access battery compartment

• AirLite[®] fits in the palm of your hand!

- Only 12 ounces (340 grams)
- 4.6 x 3 x 1.75 inches (11.7 x 7.6 x 4.4 cm)

• Features maintain sample integrity

- Constant flows up to 3000 ml/min
- Compensates up to 20 inches water back pressure at 2 L/min
- Compensates for temperature changes from 41 to 122 F (5 to 50 C)
- · Low battery and flow fault shut-off and indicator
- Rugged RFI/EMI-shielded case, CE marked

Air Life requires 1/4-inclinib tubing.	
Pump and Kits	Cat. No.
AirLite Sample Pump includes 3 AA alkaline batteries and screwdriver set	110-100*
5-pack Pump Kits High Flow Sampling includes 5 AirLite sample pumps as described above and cassette holders, in a Pelican case High Flow/Calibrator Kit includes 5 pumps as described above, cassette holders, Defender calibrator Cat. No. 717-510M, and a Pelican case High and Low Flow Sampling includes 5 AirLite sample pumps as described above, cassette holders, constant pressure controllers (CPCs), single adjustable low flow holders, and Type A tube covers, in a Pelican case	110-100K5 110-100K5-510M 110-100K5D
Accessories	
Filter Cassette Holder, accommodates two or three-part 25 or 37-mm cassettes with or without a cyclone, clips to a worker's collar	225-1
Low Flow Adapter Kit (5 to 500 ml/min) includes constant pressure controller (CPC), single adjustable low flow holder, and Type A tube cover	110-500
Protective Nylon Pump Pouch, black, with belt loop	224-902
* U.S. Patent No. 6,741,056	



SKC Limited Warranty and Return Policy

SKC products are subject to the SKC Limited Warranty and Return Policy, which provides SKC's sole liability and the buyer's exclusive remedy. To view the complete SKC Limited Warranty and Return Policy, go to http://www.skcinc.com/warranty.asp.