



Distributed by:
Air-Met Scientific Pty Ltd
Air-Met Sales/Service
P: 1800 000 744
F: 1800 000 774
E: sales@airmet.com.au

Air-Met Rental
P: 1300 137 067
E: hire@airmet.com.au
W: www.airmet.com.au



Catch the Wave

Pocket Pump TOUCH with SmartWave App

The **20 to 500 ml/min low flows** you need with the **remote connection** you want.



Intuitive **TOUCH** screen for easy operation and calibration



Bluetooth® connection for pump operation and monitoring from phones and tablets.



Air Sampling Solutions & Expertise

www.skcinc.com

Rocket Pump® TOUCH

with SmartWave App



Intuitive touch screen for easy programmability

Constant flows from 20 to 500 ml/min

- Accommodates typical flow rates for sorbent tubes

Bluetooth low energy (BLE) communication

- With PC and DataTrac® Pro Software
- With iOS or Android tablets and phones using the SKC SmartWave App
- Non-BLE pump model available

Exhaust port for direct filling of sample bags

- Optional quick-connect accessory for easy connection

Magnetic charging connector

Large backlit screen displays: Time, date, constant battery status, flow rate, sample volume, temperature, atmospheric pressure, remaining run time (programmed run), and elapsed run time

Rubber overmolding on case provides quiet operation, impact protection, and a no-slip grip

Compact and only 8.3 ounces (235 grams)

> 20+ hours run time at 500 ml/min with powerful Li-Ion battery

- Auto-dim feature conserves battery
- Extended run times with AC adapter/charger

Multi-tube sampling

- Sample with up to four tubes simultaneously; saves time and uses fewer pumps (see Accessories on page 4)
- Constant flow and pressure modes

Automatic flow fault and restart

Screen lock prevents accidental tap errors

SecureLock feature provides for passcode-secured sampling

- Also works with SmartWave App

Easy calibration with new SKC Low Flow chek-mate Calibrator



Bluetooth® communication with PC and DataTrac® Pro Software or phones/tablets with SmartWave App



USB charging with magnetic connector and sure-connect LED indicator




Exhaust port with optional quick-connect accessory for secure bag sampling



Easy calibration with Low-Flow chek-mate Calibrator

Performance Profile

Flow Range in Constant Flow Mode	20 to 500 ml/min
Compensation Range in Constant Flow Mode	20 to 500 ml/min up to 20 inches water back pressure
Pressure Range in Constant Pressure Mode	1 to 20 inches water
Flow Control System	Corrects for changes in back pressure, temperature, and atmospheric pressure
Power	Removable rechargeable Lithium-ion (Li-Ion) battery, 3.7 V, 2.6 Ah, 9.6 Wh or USB charger
Run Time (Li-Ion)	20+ hrs at 500 ml/min* up to 20 inches water back pressure, extended run times available with charger
Charging Time (varies with battery capacity and level of discharge)	≤ 10 hrs (≤ 4.5 hrs to 80%)
Accuracy	Constant flow control: ± 5% of set-point or ± 3 ml/min, whichever is higher Atmospheric pressure: ± 0.3 in Hg Temperature: ± 1 C Real-time clock: ± 1% Constant pressure mode: Reading ± 0.5 inch water
Temperature Ranges	Operating: 32 to 113 F (0 to 45 C) Charging: 32 to 113 F (0 to 45 C) Storage: -4 to 113 F (-20 to 45 C)
Humidity Range	≤ 95% RH, non-condensing
Altitude	Corrects flow for changes in temperature (32 to 113 F [0 to 45 C]) and ambient pressure up to 15,000 feet (4,572 meters) above and down to 2,300 feet (701 meters) below sea level
Flow Fault	After several seconds of restricted flow, the pump will stop running and go into flow fault mode. The pump will automatically try to restart. If flow restriction is resolved, the pump will continue the sample run. If flow restriction remains after five failed attempts at restart, the pump will stop completely and display Sample Summary.
Display Type/Parameters	High-contrast backlit LCD/Time, date, battery status, flow rate, sample volume, temperature, atmospheric pressure, back pressure, programmed run remaining time, and elapsed run time
User Interface	Eight-area capacitive touch screen with auto-dim and locking options
Dimensions	3.2 x 3.8 x 1.5 in (8.1 x 9.7 x 3.8 cm)
Weight	8.3 oz (235 gm)
Certifications/Markings	-Intrinsic safety (SKC Cat. No. 220-1000TC operated with SKC Battery Pack Cat. No. P76303)  <ul style="list-style-type: none"> Class I, Groups A, B, C, D; Class II, Groups E, F, G; Class III, T4; Class I, Zone 0, Group IIC T4; Exia -20°C ≤ T_a ≤ 45°C Ex II 1G Exia IIC T4 Ga IECEx UL 16.0113 DEMKO 16ATEX 1600 CE0539 <p>-RoHS compliant</p>
Case Material	IP 64-rated case, polycarbonate with rubberized anti-static overmolding
Communications with PC	Low-energy Bluetooth, requires DataTrac Pro for Pocket Pump TOUCH USB Bluetooth Adapter Cat. No. 877-94
Communications with iOS® or Android® Phones and Tablets	Low-energy Bluetooth, requires SmartWave App - available at the App Store and GooglePlay
Tubing	Requires 1/4-in ID tubing

* Tested using 37-mm, 0.8-µm MCE filter with new pump and battery. Pump performance may vary.

iOS is a trademark of Cisco, registered in the U.S. and other countries.
Android is a trademark of Google LLC

Pocket Pump[®] TOUCH

Publication 1925 Rev 2002

with SmartWave App

Ordering

Description		Cat. No. With BLE	Cat. No. Without BLE
Pocket Pump TOUCH only* with Li-Ion battery and screwdriver, <i>requires charger; see kits or chargers below</i>		220-1000TC	220-1000TCNB
Pocket Pump TOUCH with Charger* includes pump as described above and single charger (cable and wall cube with U.S. plug)	100-240 V	220-1000TC-C	220-1000TCNB-C
Pocket Pump TOUCH Starter Kit* includes pump and single charger as described above, 3 feet (0.9 meter) of Tygon tubing, and collar clip with cable tie	100-240 V	220-1000TC-S	220-1000TCNB-S
Single Pump Kit* includes pump and single charger as described above and Type A single tube holder, in a soft-sided nylon carry case	100-240 V	220-1000TC-K	220-1000TCNB-K
3-pack Pump Kit* includes 3 pumps as described above, 3 single chargers (cables and wall cubes with U.S. plug), and 3 Type A single tube holders, in a Pelican case	100-240 V	220-1000TC-K3	220-1000TCNB-K3
5-pack Pump Kit* includes 5 pumps as described above, 5 single chargers (cables and wall cubes with U.S. plug), and 5 Type A single tube holders, in a Pelican case	100-240 V	220-1000TC-K5	220-1000TCNB-K5
5-pack Deluxe Pump Kit* includes 5 pumps as described above, 5 Type A single tube holders, 5 single charging cables, one 5-port USB charging hub with power cable (U.S. plug), and 1 DataTrac Pro USB Bluetooth Adapter (software available via free download), in a Pelican case	100-240 V	220-1000TC-K5D	220-1000TCNB-K5D
Accessories		Cat. No.	
Single Charger , USB, magnetic connector, supplied as cable and wall cube with U.S. plug	100-240 V	220-300	
5-port USB Hub with power cable (U.S. plug) , accommodates up to 5 USB chargers, <i>requires up to 5 single charging cables available as Cat. No. P75739</i>	100-240 V	220-400	
Single Charging Cable , USB, without wall cube		P75739	
Replacement Li-Ion Battery Pack**		P76303	
Quick-connect Bag Sampling Adapter , installs on pump exhaust port for secure connection to tubing for bag sampling, accepts 1/4-inch OD PTFE tubing		220-200	
New! Low Flow chek-mate Calibrator, 20 to 500 ml/min , includes a 9-volt alkaline battery with NIST-traceable calibration certificate with UKAS-traceable calibration certificate		375-00205N 375-00205	
Single Kit Case , nylon, with shoulder strap		224-903	
5-pack Kit Case , Pelican		224-915	
DataTrac Pro for Pocket Pump TOUCH USB Bluetooth adapter , <i>required for free software download and use of DataTrac Pro Software</i>		877-94	
SmartWave App for iOS and Android phones and tablets , download directly onto device from the App Store or GooglePlay. Search on "SKC SmartWave"		N/A	

* Pocket Pump TOUCH pumps contain Li-Ion batteries and are subject to special shipping regulations.

‡ Replacing batteries with non-approved battery packs voids any warranty and UL Listing for intrinsic safety.

Pocket Pump TOUCH requires 1/4-inch ID tubing

SKC Limited Warranty and Return Policy

SKC products are subject to the SKC Limited Warranty and Return Policy, which provides SKC's sole liability and the buyer's exclusive remedy. To view the complete SKC Limited Warranty and Return Policy, go to <http://www.skcinc.com/warranty>.



Air Sampling Solutions & Expertise

www.skcinc.com