

NATURAL GAS LEAK DETECTION INSTRUMENT

FEATURES

- LASER Technology
- Specific to Methane
- ATEX Certified - Zone 1
- Wide Measurement Range (0 ppm to 100% volume)
- Integral GPS and Bluetooth
- Accurate Reporting
- Lightweight
- Hot Swap Battery

BENEFITS

- No Flame, No Hydrogen
- No cross-gas effects or False Readings
- Intrinsically Safe
- Highly accurate
- Maintains Compliance
- Multiple Reporting Functions
- Easy to Use
- All Day Operation



HAND-HELD LASER BASED NATURAL GAS LEAK DETECTION INSTRUMENT

The **LASER ONE** is a portable natural gas leak analyser with LASER spectroscopy. This highly sensitive detector offers all the advantages of optical detection in a compact and portable device. The HUBERG LASER ONE gives you precise and reliable findings when detecting methane leaks.

LASER ONE

LED Alarm Lights

4 Visual Alarm Lights & Impact Bumpers

Status Indicators

- Measurement Mode
- Pump
- PC Communications
- Battery Level

Function Button

Pump and GPS Control

Audio Alarm

~65 dB Alarm

Jog Dial

- Threshold
- PPM
- LEL
- ON/OFF Absolute
- ON/OFF GPS
- Save Leak
- Memory

Methane Detection

Integral GPS
Highly Accurate
Rapid Response



POWER SUPPLY			
Battery type	Li-ion rechargeable battery pack (user replaceable)	Battery charger	Separate intelligent battery charger powered from mains supply (100-240V, or via vehicle power outlet)
Battery life	Typical 10 hours from fully charged (with backlight activated)	Charge time	Approximately 4.5 hours from complete discharge
GAS RANGES			
Gases Measured	CH ₄	Range	1-9,999ppm / 1%-100% (Vol)
Response time	Without Probe : T ₉₀ = 2 seconds With Probe : T ₉₀ = 3.5 seconds		
Accuracy	0.1ppm-10.9ppmVol: +/-1.0ppm	11-9,999ppmVol: +/- 10% of reading	1%-100%Vol +/- 10% of reading
Resolution	0.1ppm / 0.1% (Range dependent)	Minimum detectable limit	0.3ppm
PUMP			
Flow	Minimum : 0.6 L/Min	Typical : 0.8 L/Min	Maximum : 1.0 L/Min
ENVIRONMENTAL CONDITIONS			
Operating Temperature	-25 to 50°C / -13 to 122° F	Humidity Range	5% to 80% Relative Humidity (non-condensing)
Atmospheric Pressure/ Range	1013mbar +/-100mbar/29.91 inHg +/- 2.95inHg	Protection Level	IP65
PHYSICAL			
Weight	1.3 kg / 2.9 lb	Environmental Storage Conditions	Humidity <95% Temperature -40°C to +60°C/-40°F to 140°F
Dimensions	229 x 97 x 109 mm / 9 x 4 x 4.2 inches		
Alarm Sound Level	~65 dB (A) @30cm / 12"	User Interface	<ul style="list-style-type: none"> • Display (LxH): 86 x 47mm / 3.39" x 1.85" • Jogdail: Scroll menu for rapid and easy selection of menu items. • 3 Function Keys
Gas Connections	Quick Release Coupler	Electrical Connections	Multiway adaptor for battery charger and USB communication port with a PC
		Carry Strap	30mm/1.2" wide synthetic woven strap
CERTIFICATION RATING			

©2021 Product designs and specifications are subject to change without notice. User is responsible for determining suitability of product.

QED Environmental Systems Inc.
2355 Bishop Circle West Dexter, MI 48130, USA



Data Sheet Reference : TDS-2411 (Issue 02)

info@qedenv.com

800.624.2026
734.995.2547

WWW.QEDENV.COM

sales@qedenv.co.uk

+44 (0) 333 800 0088