

Measuring electric fields from 3 MHz to 18 GHz

using instruments in the NBM-500 family

- ▲ **General public and occupational field exposure from radio broadcasting, telecoms, and radar**
- ▲ **Isotropic (non-directional) measurement**
- ▲ **62 dB dynamic range without changing measurement range**

The probe contains three orthogonally arranged dipoles with detector diodes. The three voltages, corresponding to the spatial components, are available individually at the probe output. The NBM basic unit calculates the resulting isotropic field strength.

APPLICATIONS

The probe detects electric fields from 3 MHz to 18 GHz, covering the fields generated by broadcasting, telecoms, and radar. The dynamic range from 0.6 V/m up to 800 V/m (62 dB) makes the probe ideal for measuring exposure in both the general public and the occupational environment.

PROPERTIES

The probe is designed with mechanical and electrical properties ideal for field use. The probe head is made of foam material to provide effective protection for the sensors, while having excellent RF characteristics. The electric destruction limit of 1,100 V/m for continuous wave signals is several times higher than any of the human safety limit values.

CALIBRATION

The probe is calibrated at several frequencies. The correction values are stored in an EPROM in the probe and are automatically taken into account by the NBM instrument. Calibrated accuracy is thus obtained regardless of the combination of probe and instrument.



SPECIFICATIONS ^a

Probe EF1891		Electric (E-)Field	
Frequency range ^(b)	3 MHz to 18 GHz		
Type of frequency response	Flat		
Measurement range	0.6 to 800 V/m (CW) 0.6 to 65 V/m typ. (True RMS)	0.1 $\mu\text{W}/\text{cm}^2$ to 170 mW/cm^2 (CW) 100 nW/cm^2 to 1,12 mW/cm^2 (True RMS)	
Dynamic range	62.5 dB		
CW damage level	1100 V/m	320 mW/cm^2	
Peak damage level ^(c)	1400 V/m	520 W/cm^2	
Sensor type	Diode based system		
Directivity	Isotropic (Tri-axial)		
Readout mode / spatial assessment	3 separate axes		
UNCERTAINTY			
Flatness of frequency response ^(d) Calibration uncertainty not included	typ. +2 dB/-2 dB @ 3MHz typ. -3 dB @ 18 GHz +1/-1,5 dB (10 MHz to 3 GHz) +2/ -1,5 dB (>3 GHz to 11 GHz)		
Linearity Referred to 0.2 mW/cm^2 (27.5 V/m)	± 2 dB (0,6 to 4 V/m) $\pm 0,5$ dB (4 to 300 V/m) ± 2 dB (300 to 800 V/m)	± 2 dB (0,1 to 4,2 $\mu\text{W}/\text{cm}^2$) $\pm 0,5$ dB (4,2 $\mu\text{W}/\text{cm}^2$ to 24 mW/cm^2) ± 2 dB (24 mW/cm^2 to 170 mW/cm^2)	
Isotropic response ^(e)	± 1 dB (10 MHz to 5 GHz) $\pm 2,25$ dB (>5 GHz to 11 GHz)		
Temperature response	+0.2/ -1.5 dB (± 0.025 dB/K @ 10 to 50 °C)		
GENERAL SPECIFICATIONS			
Factory calibration frequencies	3/ 10/ 27.12/ 100/ 200/ 300/ 500/ 750 MHz 1/ 1.8/ 2.45/ 3/ 4/ 5/ 6/ 7/ 8.2/ 9.3/ 10/ 11/ 18 GHz		
Recommended calibration interval	24 months		
Temperature range	Operating 0 °C to +50 °C Non-operating (transport) -40 °C to +70 °C		
Humidity	5 to 95 % RH @ ≤ 28 °C	≤ 26 g/m^3 absolute humidity	
Size	318 mm x 66 mm \emptyset		
Weight	90 g		
Compatibility	NBM-500 series meters		
Country of origin	Germany		

- (a) Unless otherwise noted specifications apply at reference condition: device in far-field of source, ambient temperature 23 ± 3 °C, relative air humidity 25% to 75%, sinusoidal signal
 (b) Cutoff frequency at approx. -3 dB @ 3 MHz/ -4 dB @ 18 GHz
 (c) Pulse length 1 μsec , duty cycle 1:100
 (d) Frequency response can be compensated for by the use of correction factors stored in the probe memory
 (e) Results are calculated from the maximum and minimum response obtained during the full revolution about the stem of the probe, oriented 54.7° to the electric field vector.

ORDERING INFORMATION

	Part number
Probe EF1891, E-Field for NBM, 3 MHz – 18 GHz, Isotropic	2402/02C
Probe EF1891, E-Field, ACC - with accredited (DAkkS) calibration, basic unit required	2402/02C/ACC

Narda Safety Test Solutions GmbH
 Sandwiesenstrasse 7
 72793 Pfullingen, Germany
 Phone +49 7121 97 32 0
 info@narda-sts.com

Narda Safety Test Solutions
 North America Representative Office
 435 Moreland Road
 Hauppauge, NY 11788, USA
 Phone +1 631 231 1700
 info@narda-sts.com

Narda Safety Test Solutions S.r.l.
 Via Benesse, 29
 17035 Cisano sul Neva SV, Italy
 Phone +39 0182 586 41
 nardait.support@narda-sts.it

Narda Safety Test Solutions GmbH
 Beijing Representative Office
 Xiyuan Hotel, No. 1 Sanlihe Road, Haidian
 100044 Beijing, China
 Phone +86 10 6830 5870
 support@narda-sts.cn

www.narda-sts.com

® Names and Logo are registered trademarks of Narda Safety Test Solutions GmbH - Trade names are trademarks of the owners.