

Geotech BP Controller 300/500 PSI

The simple-to-use Bladder Pump (BP) Controller (300 or 500 PSI) utilizes accurate microprocessor-controlled fill/discharge timers to sustain true low-flow sampling techniques. Both Controllers are equipped with high-pressure valves and fine resolution regulators that can perform in deep-well applications.

The Geotech BP Controller universally connects to any bladder pump system using simple quick-connect adapters. The BP 300 controller can also operate two bladder pumps simultaneously with an optional airline splitter.

FEATURES

- Designed for durable, trouble-free operation
- High pressure operation for greater depths
- Multiple power input options
- Microprocessor controlled timers for accuracy
- Internal over-pressure protection
- Battery over-draw protection
- Water Level Meter compatibility for well draw-down
- Intuitive user controls and status indicator
- Accessories cavity for easy portability
- Included: Air-In and Air-Out Hoses, AC Power Supply, DC Power Cord and Clip Adapter, Geotech Drawstring Bag, Carry Case
- Optional 2-pump airline splitter



**BP Controller 300 PSI
with optional draw-down control
for low-flow sampling**



Geotech BP Controller 500 PSI



Geotech BP Controller 300 PSI

SPECIFICATIONS

	300 PSI	500 PSI
Performance		
Operating Depth	0-690 feet (210 m)	0 -1000 feet (0-305 m)
Input Air Pressure	Up to 300 psi (20.5 bar)	100 to 500 psi (34 bar)
FILL Timer Range	5 - 120 seconds	5 - 180 seconds
DISCHARGE Timer Range	5 - 120 seconds	5 - 180 seconds
Timer Resolution	2 seconds	2 seconds
Timer Accuracy	±2 seconds	±3 seconds
12V 8Ah Battery Life	1,300 cycles @ 30 sec. timers	50,000 cycles
Internal Battery/Life	External only	(2x) 9V/30,000 cycles
Environmental		
Operating Temperature	32°-158°F (0°-70°C)	32°-158°F (0°-70°C)
Storage Temperature	-40°-185°F (-20°-85°C)	-40°-185°F (-20°-85°C)
Physical		
Enclosure	7" x 16" x 12" (18 x 41 x 30.5 cm)	7" x 19" x 14" (18 x 48 x 35 cm)
Weight	15 lbs. (6.8 kg)	25 lbs. (11.4 kg)
Enclosure Material	Structural resin	Structural resin
Input Power		
External Battery	10.5-13.8V DC	10.5-26V DC
AC	90-240V AC*	90-240V AC*
Line Frequency	45-65 Hz	45-65 Hz
Maximum Power	15 Watts	15 Watts pulse for 50mS

*International AC Power Plug Adapters available (UK, AUS, EURO)



CALL GEOTECH TODAY (800) 833-7958

Geotech Environmental Equipment, Inc.

2650 East 40th Avenue • Denver, Colorado 80205

(303) 320-4764 • FAX (303) 322-7242

email: sales@geotechenv.com • website: www.geotechenv.com



Distributed by:
Air-Met Scientific Pty Ltd

Air-Met Sales/Service
P: 1800 000 744
F: 1800 000 774
E: sales@airmet.com.au

Air-Met Rental
P: 1300 137 067
E: hire@airmet.com.au
W: www.airmet.com.au

bp_controller.qxp 04/13/20