

Geotech ET and ETL Portable Water Level Meters

The Geotech ET and ETL Portable Water Level Meters are designed to provide reliable and accurate measurements of groundwater levels. Water level readings are conveniently taken at the top of the casing with accuracy to within 1/100 of a foot.

FEATURES

- ET has an extremely durable polypropylene storage reel with rugged solid aluminum frame
- ETL is on a lightweight steel and aluminum storage reel for easy transportation and durability in the field
- Highly accurate Polyethylene coated steel tape marked in engineering or metric increments
- Field serviceable 5/8" (1.59cm) probe with stainless steel conductors for durability
- An optional 3/8" (.95cm) non-field replaceable probe is available
- Adjustable sensitivity to prevent false triggering
- Audible and visible alarms activated when the probe makes contact with water
- Easily replaced 9 volt battery
- Water resistant padded carrying case to protect instrument (optional)
- Built in reel hanger on ET models and included Leader Guard for longer tape life
- MDPE and ETFE coated steel tape available upon request
- Optional tape weight helps sink probe into a deep or crooked well



Geotech ETL



5/8" (1.59cm) Field Replaceable Probe



Optional 3/8" (1cm) Probe



Optional White MDPE Tape



Geotech ET with optional bag and tape weight

SPECIFICATIONS

| | | |
|--------------|---------------------------|--|
| Size: | ET Reel | 13" H x 11" W x 7" D (33cm H x 28cm W x 18cm D) |
| | ETL 500' Reel | 14.5" H x 9" W x 11.5" D (37cm H x 23cm W x 29cm D) |
| | ETL 750/1000' Reel | 15.75" H x 13" W x 11.5" D (40cm H x 33cm W x 29cm D) |
| | Probe | 5/8" O.D. x 6 1/8" L (1.59cm O.D. x 15.56cm L) 3/8" O.D. x 6 1/2" L (optional) 1cm O.D. x 16.5cm L |

| | | |
|-----------------------------|------------|--|
| Length & Weight: | ET | 100' (30 m) = 9 lbs. (4 kg) 200' (60 m) = 11 lbs. (5 kg) 300' (100 m) = 14 lbs. (6.3 kg) |
| | ETL | 500' (150 m) = 20 lbs. (9 kg) 750' (225 m) = 24 lbs. (10.9 kg) 1000' (300 m) = 28 lbs. (12.7 kg) |

| | | |
|------------------|----------------|--|
| Accuracy: | ET Tape | 100th of a foot / 100' (Per Federal Specification GGG-T-106E) |
|------------------|----------------|--|

| | | |
|------------------|--------------|---|
| Material: | Reel | Polypropylene and aluminum (ET) Powder coated steel and aluminum (ETL) |
| | Tape | Polyethylene coated steel |
| | Probe | Stainless Steel, Acetal, Buna-N |

| | |
|---------------|----------------------------|
| Power: | 9 Volt DC alkaline battery |
|---------------|----------------------------|

| | |
|---------------|--------------------|
| Alarm: | Audible and visual |
|---------------|--------------------|

| | |
|------------------|--------|
| Warranty: | 1 year |
|------------------|--------|

| | |
|------------------------|----|
| Certifications: | CE |
|------------------------|----|

CALL GEOTECH TODAY (800) 833-7958

Geotech Environmental Equipment, Inc.

2650 East 40th Avenue • Denver, Colorado 80205

(303) 320-4764 • FAX (303) 322-7242

email: sales@geotechenv.com • website: www.geotechenv.com



Distributed by:
Air-Met Scientific Pty Ltd

Air-Met Sales/Service
P: 1800 000 744
F: 1800 000 774
E: sales@airmet.com.au

Air-Met Rental
P: 1300 137 067
E: hire@airmet.com.au
W: www.airmet.com.au

geotech_et_etl_wlm.qxp 07/28/20