

Oil and Water Level Meters

Geotech Interface Probe With Float

The Geotech Interface Probe With Float is a portable, reel-mounted instrument that provides measurements of liquids lighter and heavier than water. When the probe is lowered down a well and contacts the product layer, a solid tone and red light alarm is activated at the reel. When the probe detects water, the tone begins to oscillate and the light changes to green.

FEATURES

- Extremely durable polypropylene storage reel with rugged aluminum frame
- · HDPE coated steel-core dog bone shaped tape
- Highly visable printed markings in engineering or metric units
- PTFE and stainless steel probe with spring strain relief
- Audible and visible alarms activated on reel when probe contacts product and water
- · Auto shut-off circuit to extend battery life
- Easily replaced 9 volt battery
- Water resistant padded carrying case to protect instrument
- Built in reel hanger and included Leader Guard for longer tape life.



Geotech Interface Probe With Float includes padded carrying case and Leader Guard

SPECIFICATIONS

Size:	Reel Probe	13" H x 11" W x 7" D (33 cm H x 30 cm W x 18 cm D) 1.5" O.D. x 8.9" L (3.8 cm O.D. x 22 cm L)
Length / Weight:		100' (30 m) = 9 lbs. (4 kg) 200' (60 m) = 11 lbs. (5 kg) 300' (100 m) = 14 lbs. (6 kg)
Accuracy:		1/100 of a foot per 100 feet (3mm/30.5 meters) per Federal Specification GGG-T-106E
Material:	Reel Tape Probe	Polypropylene and aluminum HDPE coated steel-core tape PTFE, Viton® and stainless steel
Resolution:		Imperial units 1/100 per foot, metric units 1mm
Power:		9 Volt DC alkaline battery
Alarm:		Audible and Visual
Warranty:		1 vear

CALL GEOTECH TODAY (800) 833-7958

Geotech Environmental Equipment, Inc.

2650 East 40th Avenue • Denver, Colorado 80205 (303) 320-4764 • FAX (303) 322-7242 email: sales@geotechenv.com • website: www.geotechenv.com

