# **Geotech Portable Water Level Meters + Temperature**

ir-Met Renta

P: 1300 137 067

E: hire@airmet.com.au W: www.airmet.com.au

Distributed by: Air-Met Scientific Pty Ltd Air-Met Sales/Service

1800 000 744

F: 1800 000 774 E: sales@airmet.com.au

The Geotech Portable Water Level Meters + Temperature are designed to provide reliable and accurate measurements of groundwater levels and temperature. Readings are conveniently taken at the top of the casing with accuracy to within  $\frac{1}{100}$  of a foot and  $\pm 1^{\circ}$ F (temperature accuracy).

# **FEATURES**

- Mounted on a lightweight steel and aluminum storage reel for easy transportation and durability in the field
- Highly accurate HDPE coated steel tape marked in engineering or metric increments
- Field replaceable 5%" (1.59cm) probe with stainless steel conductors for durability
- · Adjustable sensitivity to prevent false triggering
- Audible and visible alarms activated when the probe makes contact with water
- Easily replaced 9 volt battery
- Water resistant padded carrying case to protect instrument
- Optional tape weight helps sink probe into a deep or crooked well



Geotech Water Level Meter + Temperature Face Plate

5/8" (1.59cm) Field Replaceable Probe

### CALL GEOTECH TODAY (800) 833-7958

#### Geotech Environmental Equipment, Inc.

2650 East 40th Avenue • Denver, Colorado 80205 (303) 320-4764 • FAX (303) 322-7242 email: sales@geotechenv.com • website: www.geotechenv.com



Water Level Meters

Geotech Water Level Meter + Temperature and Padded Carry Case

# **SPECIFICATIONS**

Size:	100'-500' Reel	15" H x 11.5" W x 10.5" D (38cm H x 29cm W x 27cm D)
	750'-1000' Reel	15" H x 11.5" W x 14.5" D (38cm H x 29cm W x 37cm D)
	Probe	5⁄8" O.D. x 6 ⅓" L (1.59cm O.D. x 15.56cm L)
Length & 100' (30 m)		
Weight	· · ·	
	300' (100 m)	
	500' (150 m)	
	750' (225 m)	
	1000' (300 m)	28 lbs. (12.7 kg)
Accuracy: Tape		100th of a foot/100'
		(Per Federal Specification GGG-T-106E)
Temperature Sensor		± 1°F (0.5°C)
Materia	al: Reel	Powder coated steel and aluminum
	Таре	HDPE coated steel
	Probe	Stainless Steel, Buna-N, Acetal
Power:		9 Volt DC alkaline battery
Alarm:		Audible and visual
Warranty:		1 year
Certifications:		CE