



Well Wizard ZERO™ and Clear™

PFAS-Free Dedicated Bladder Pump Systems



The industry's first dedicated pumps designed for PFAS sampling

The Well Wizard ZERO and Clear dedicated bladder pump systems from QED give you the high sample accuracy and proven reliability of our Well Wizard dedicated in a PFAS-free configuration that meet PFAS sampling program requirements and regulatory guidance. Based on our P1100 Series bladder pumps that have been in use for nearly 40 years, the ZERO and Clear models are constructed of materials that have been tested for PFAS leaching in water at the lowest available laboratory detection and reporting limits for 24 PFAS compounds.*

- ZERO models are made entirely without fluoropolymers, using a proprietary fluorine-free bladder developed by QED to provide exceptional flex life of up to 50 years†
- Clear models use QED's long-life DuraFlex PTFE bladder, tested and certified to be PFAS-free, with all other components fluorine free
- ZERO and Clear models are tested for PFAS, VOCs and SVOCs, and each pump is certified PFAS-free
- Fits into 2" ID (50MM) and larger well casings and can be installed to depths of 600 feet (183 m)
- Sample from nearly unlimited depths using optional drop tube inlet tubing and weight kits
- QED's twin-bonded HDPE tubing meets PFAS sampling requirements and is tested for VOCs & SVOCs
- ZERO models covered by QED's 5-year warranty, and Clear models covered by a 10-year warranty



© Product designs and specifications are subject to change without notice. User is responsible for determining suitability of product.

QED Environmental Systems Inc.
2355 Bishop Circle West Dexter, MI 48130, USA



info@qedenv.com



800.624.2026
734.995.2547



WWW.QEDENV.COM

QED Environmental Systems Ltd.
Cyan Park, Unit 3 Jimmy Hill Way, Coventry CV2 4QP, UK



sales@qedenv.co.uk



+44 (0) 333 800 0088



Available for Rental at:
Air-Met Scientific Pty Ltd

Air-Met Sales/Service P: 1800 000 744 F: 1800 000 774 E: sales@airmet.com.au	Air-Met Rental P: 1300 137 067 E: hire@airmet.com.au W: www.airmet.com.au
---	--

Well Wizard ZERO and Clear Pump Specifications

ZERO Pump materials: PVC body, inlet and discharge housings, and inlet screen; polypropylene or stainless steel fittings, proprietary fluorine-free bladder, acetal check balls, EPDM O-rings

Clear Pump materials: PVC body, inlet and discharge housings, and inlet screen; polypropylene or stainless steel fittings, PTFE bladder, acetal check balls, EPDM O-rings

Length: Standard length models = 41.0" (104 CM) Short body models = 20.0" (50 cm)

Outside Diameter: 1.66" (42mm)

Fitting Type: Standard pressure = polypropylene compression type High pressure = stainless steel compression type

Tubing Diameter: Standard length models = 3/8" OD + 1/4" OD twin-bonded discharge and air supply tubing
 Short body models = 1/4" OD + 1/4" OD twin-bonded discharge and air supply tubing

Inlet Housing Thread Diameter: 3/8" Female NPT

Bladder Volume: Standard length = 395 ml (13.4 oz, 0.10 gal) Short body = 130 ml (4.4 oz, 0.03 gal)

Maximum operating pressure: 300 PSI (20.7 bar, 2,068 kPa)

Maximum lift depth: 600 feet (183m)

Well Wizard ZERO and Clear Pump System Components

- 37789** PVC slotted inlet screen for standard length pump models
- 37727** PVC slotted inlet screen for short body pump models
- P5000** Twin bonded HDPE pump tubing, 3/8" OD + 1/4" OD discharge and air supply
- P5200** Twin bonded HDPE pump tubing, 1/4" OD + 1/4" OD discharge and air supply
- C Series** Recessed well cap for 2" (50mm) and 4" (100mm) nominal ID Well Casings
- 2120 Series** External slip cap for 2" (50mm) and 4" (100mm) nominal ID Well Casings
- 37739** MicroPurge flexible well cap discharge adapter for 1/4" OD discharge tubing, 3 feet long (90 cm)
- 37740** MicroPurge flexible well cap discharge adapter for 3/8" OD discharge tubing, 3 feet long (90 cm)

Optional drop tube inlet kits available for sampling at depths below 600 feet or to allow use of standard pressure models at greater sampling depths. Contact QED for more information and proper selection of drop tube kits and additional weights.

** PFAS testing is conducted by soaking all pumps in water for 24 hours and collecting samples from the soak tank, along with blank samples collected during tank filling. Samples are analyzed for 24 different PFAS compounds using US EPA Method 537M, with method detection limits below 1 ng/L and reporting limits of 5 ng/L or less for most PFAS. Results must be non-detect for all 24 PFAS compounds at the laboratory reporting limits (RLs). Based on this, Well Wizard ZERO and Clear pump models should not contribute any PFAS to ground water samples collected with these products.*

† Based on a pump operating at 4 cycles per minute for 60 minutes and used 4 times per year. ZERO model bladders have been tested to an average of over 50,000 cycles without failure. Overall life may vary based on usage and water quality.

© Product designs and specifications are subject to change without notice. User is responsible for determining suitability of product.

QED Environmental Systems Inc.
2355 Bishop Circle West Dexter, MI 48130, USA



info@qedenv.com



800.624.2026
734.995.2547



WWW.QEDENV.COM

QED Environmental Systems Ltd.
Cyan Park, Unit 3 Jimmy Hill Way, Coventry CV2 4QP, UK



sales@qedenv.co.uk



+44 (0) 333 800 0088